

	US	Metric	SP-40		SP-60		SP-100	
Overall Dimensions								
A - Width	inch	mm	36.3	992	39.5	1003	47.3	1201
B - Depth	inch	mm	43	1092	48.4	1229	54.9	1394
C - Height	inch	mm	57.6	1463	63.6	1615	71.2	1809
Net Weight	lb	kg	1330	605	1580	718	2350	1068
Shipping Weight	lb	kg	1350	614	1600	727	2370	1077
Shipping Volume	cu ft	cu m						
Wash Cylinder Information								
Diameter	inch	mm	26.8	680	31.1	790	37	940
Depth	inch	mm	20.3	515	22	560	27.2	690
Volume	cu ft	liters	6.6	187	9.7	274	16.9	478
Perforation Diameter	inch	mm						
Capacity, 1:10 fill ratio	lb	kg	41	18.7	60	27.4	105	47.8
Motor								
Size	HP	kW	3	2.2	5	3.7	7.5	5.5
Cylinder Speeds (See note below):								
Wash	rpm	g	46	0.8	43	0.8	39.5	0.8
Distribution	rpm	g	73	2	67	2	62	2
Intermediate extraction	rpm	g	629	150	583	150	540	150
High extract 1	rpm	g	725	200	673	200	624	200
High extract 2	rpm	g	811	250	753	250	698	250
High extract 3	rpm	g	960	350	890	350	825	350
Door Opening								
Door Opening Diameter	inch	mm	15.7	400	17.7	450	19	483
Height to bottom of door	inch	mm	22.1	561	25.3	642.62	27.6	701
Drain System								
Overflow Size	inch	mm	1.5	38.1	1.5	38.1	1.5	38.1
Drain Outlet Size	inch	mm	3	76.2	3	76.2	3	76.2
Number of Drain Outlets	standard	optional	1	2	1	2	1	2
Water Inlet								
Connection Size	NPT		3/4 NPT		3/4 NPT		1 NPT	
Number of Inlets	standard	optional	2	3	2	3	2	3
Chemical Supply System								
Number of Dry Chemical Compartments	standard	optional	1	5	1	5	1	5
Number of Liquid Supply Connections	standard	optional	6	8	6	8	6	8
Liquid Supply Connection Size	NPT		1/2 NPT		1/2 NPT		1/2 NPT	
Electrical Connections								
Max. Circuit Breaker Size	200-240V, 3Ø		15		15		40	
Max. Circuit Breaker Size	380-480V, 3Ø		15		15		25	

Note: Wash and Extract speeds are fully programmable. The values shown are examples.

Our Policy is one of ongoing improvements. Specifications are subject to change without notice.