

Model			DI-200		DI-225		DI-325	
<b>Capacity</b>	lbs	kg	200	91	225	102	325	148
<b>Cylinder</b>								
Diameter	in	mm	62.5	1588	63.75	1620	63.75	1620
Depth	in	mm	42	1067	48.8	1240	60.7	1541
Volume	cu ft	liters	74.5	211	90.23	255	112.2	317
<b>Basket Motor</b>	HP	kW	3	2.25	3	2.25	5	3.75
<b>Blower Motor (Gas)</b>	HP	kW	7.5	5.6	10	7.5	15	11.25
<b>Blower Motor (Steam)</b>	HP	kW	15	11.25	15	11.25	20	15
<b>Utility Requirements</b>								
Steam Consumption	lbs	kg	890	405	925	420	1125	511
Steam Supply	Male NPT		2"		2"		2"	
Steam Return	Male NPT		2"		2"		2"	
Air Flow	CFM	cmm	6,500	184	7,400	210	8,800	250
Compressed Air Volume	cu ft/hr	cu m/hr	6	0.17	7	0.2	11	0.3
Air Connection	Female NPT		1/8"		1/8"		1/8"	
Gas Requirements	btu/hr	lcal/hr	750,000	189,000	800,000	201,600	1,130,000	284,760
Gas Flow	CFM	cmm	5,300	150	6,000	170	6,700	189
Gas Connection	Female NPT		1-1/4"		1-1/4"		1-1/4"	
<b>Dimensions</b>								
<b>A - Height</b>	in	mm	128	3239	114.25	2309	113.15	2874
<b>B - Height (Tilted)</b>	in	mm	138.2	3510	124.4	3160	124.3	3157
<b>C - Depth</b>	in	mm	75.5	1918	75.8	1926	75.8	1926
<b>D - Depth (Tilted)</b>	in	mm	83	21.8	83.5	2120	95.3	2420
<b>E - Width</b>	in	mm	55.5	1410	59.5	1511	79.8	2028
<b>F - Mounting Width</b>	in	mm	65.98	1676	65.98	1676	65.98	1676
<b>G - Mounting Depth</b>	in	mm	46	1168	52.6	1336	64.6	1640
Net Weight	lbs	kg	3719	1687	3820	1736	4250	1932